

Model		
System	72V/7.5KW Series	

Key Components			
Battery	12 x 6V Q lead-acid battery (210AH)		
Motor	7.5KW motor		
Controller	Curtis 1205M		

Performance			
Passenger Capacity	14		
Range (loaded) based on flat road at a speed of 20km/h (km)*	>70		
Max. speed (km/h), no load	30		
Minimum turning radius (m)	5.35		
Max. climbing ability (loaded)	25%		
Max. movement after brake at speedof 20km/h	≤4m		
Net weight	1120kgs		

Steering and Suspension				
Steering system	Rack and pinion drive			
Right hand drive system	Electrical power steering			
Brake system	Four wheel hydraulic drum brake+hand parking brake			
	Front disc brake and rear drum brake, with vacuum booster (Optional)			
Transmission system	Automatic drive system (stepless speed change)			
Front suspension	Independent suspension			
Rear suspension	Integral rear axle, coil spring non-independent suspension, hydraulic shock absorber tube			
Wheel & Tyre	4J*12 Aluminum wheel, wheel cap, 155R12,8PR			

## **OUTSTANDING SPECIFICATIONS AND EXCEPTIONAL WARRANTY**

Based on advanced German engineering and design all Hulikkal models feature the industry's leading U.S.A. and European brand electrical and mechanical components are backed by an exceptional warranty.

1 Year on Battery

2 Years on Controller & Charger®

5 Years on Motor & Axle 
Against any Manufacturing Defects

Dimensions			
Overall dimensions (mm)	5100x1535x2070mm		

	Body and Frame	
Frame	Welded steel framework with sand blasting+paint treatment	
Body	Steel frame + fiberglass	
Roof	Fibreglass+aluminum frame, with roof handle	
Door	Aluminum structure + tempered glass	
Windshield	Laminated glass	
2point seat belt	10pcs (Optional)	
3point seat belt	14 pcs (Optional)	
Enclosure	PVC (Optional)	
Seats	High quality of artificial leather	
Floor	Non-slip floormat	
Inner rear view mirror	One piece per cart in the middle of the windshield (Optional)	
Side rear view mirror	Two pieces per cart	

Electric system			
Lighting system and horn Reversing alarm	Front: 2 Headlights (High beam and dipped headlight), 2 front turn signals, 2 fog lights; Back: 2 rear turn signals, 2 taillights[position] light & Sake light), 1 fog light, 1 reverse light),with DC-DC converter (converting from 48V to 12V), horn.		
Instruments on dashboard	Combination instrument including power consumption, voltage, current, speed, mileage, time, light, F/R switch, and signal.		
Audio System	CD and Radio, speakers		
Microphone	Wired (Optional)		
Switch assembly	Combination switch including Power kety, Light and wiper combination switch, F/R switch and reverse buzzer switch		
Solar panel	8V/230W (Optional)		
	72V/270W (Optional)		
Charger	Non-onboard charger, china origin, input 110V-240V~50Hz-60Hz, output 48V, 25A		

Standard Body Color (customized color if available, but extra cost should be paid

Januaru	Jour Color (custo	Jillized Color	ii avallable, but t	XIII COSC SIIC	(alev.com
Pure White	Pearl White	Pearl Red	Greece Yellow	Lake Green	Pure Black

Standard Seat Color

All the color showed here is just for reference!
The real color of the car may look different as showed here!